









4G PRIMARY CELLULAR ALARM COMMUNICATOR

PRIMARY COMMUNICATIONS

The Uplink 4530 includes the latest 4G technology for the best performance and longest life cycle. Compatible with 2G, 3G and 4G cellular networks, the 4530 also operates on redundant networks for maximum reliability. The 4530 is designed to be utilized as a full alarm event primary communicator. All major formats are supported for compatibility with virtually all alarm systems and central stations. Installation of the Uplink 4530 is remarkably easy with the use of a secure website and unit switch settings. Activation is instant and is available using the dealer website or by a live operator.

KEY FEATURES:

-  Primary 4G Cellular communications, full alarm/event reporting
-  Power from the panel or separate 12V DC power supply
-  Installs in minutes with complete end-to-end signal verification
-  Contact ID, SIA, Modem Ite/IIIa/IIIa², or Pulse 4/2 (:10, :20, or :40 PPS)
-  Instant activation by secure dealer website or live operator and email notifications for instant alerts
-  Eligible for Uplink Lifetime Guarantee



SUPPORTS UPLINK REMOTE FOR INTERACTIVE CONTROL

UPLINK 4530 DEVICE FEATURES:

- ✓ Perfect for residential alarm systems
- ✓ “Out-of-the-box” operation - no special programmer or central station equipment is required
- ✓ Power from the panel, battery, or other 12V DC power source
- ✓ Remote on-demand testing for status and signal strength
- ✓ Live technical and activation support 8:00 a.m. to 8:00 p.m. EST, Monday through Friday
- ✓ Customizable product marketing services through a simple e-commerce website
- ✓ Flat-rate billing for improved dealer profitability
- ✓ Supports Uplink Remote, momentary or maintained keyswitch zones. No adapter board required.
- ✓ Login @ uplinkremote.com for remote control

A TRUSTED PARTNER

The Uplink 4530 is a new member of the Uplink family of alarm communicators. Our products deliver the unique combination of technology, quality, options and superior value that has made Uplink the security industry's most trusted source for alarm communicators since 1996. Uplink options include 4G, 2G, CDMA or broadband communicators, primary or backup units, signaling only or Uplink Remote services, one year warranty or optional Lifetime Guarantee, summary or full event reporting, service in the U.S. or Canada, and different power choices to fit the needs of each installation. With hundreds of thousands of installed communicators throughout the United States and Canada, Uplink has the experience and expertise to provide the most reliable products and the finest support.

Plus, Uplink wireless communicators are backed by the unique combination of the proprietary ISO-27001 certified network service offering and an advanced dealer web management tool.

For more information, visit the Uplink website and sign up to become an Uplink dealer at www.uplink.com.



UPLINK 4530
 PRIMARY ALARM COMMUNICATOR
 12V DC Required

INPUTS	
Alarm Dial Capture	Full event reporting of Contact ID, SIA, Modem IIe/IIIa/IIIa ² , or Pulse 4/2 (:10, :20, or :40 PPS) Internet or Dialup
OUTPUTS AND REPORTING	
Central Station	Contact ID, SIA, Modem IIe/IIIa/IIIa ² , or Pulse 4/2 (:10, :20, or :40 PPS) Internet or Dialup
Three Relay Outputs	Configurable - normally closed
Other Reporting Methods	Email, Text Message, Uplink Remote
Automated Testing	Monthly, Weekly, or Daily
Status LEDs	<ul style="list-style-type: none"> • Signal Strength • Power • Panel Hook Status • Trouble • Heartbeat
POWER REQUIREMENTS	
12V DC (200 mA constant, 600 mA peak)	Uninterrupted Class 2 Power Supply 12V DC/600 mA minimum required
RADIO	
4G (HSPA+)	Compatible with 2G, 3G and 4G GSM networks
Cellular Frequencies	850/1900 MHz
Transmit Power	Maximum allowable: <ul style="list-style-type: none"> • 1.0W at 1900 MHz • 2.0W at 850 MHz
DIMENSIONS	
Height/Width/Depth (inches)	10.5/5.4/2.5
Antenna	3.75 inches